

Paint Removal Agent

Technical Datasheet

Description

Paint Removal Agent (PRA) is a cleaning product specifically developed for the removal of paint residues from glass surfaces of solar panels. The formula of this solution is designed to be as mild as possible with the solar panels, so that it is easy to use and does not present any health risks for professionals.

Dilution specifications

Water-based spray paint - 1:5 (1kg of PRA for 5 liters of water)
Outdoor coatings, interior paints, wood coatings, multi-surface enamels - 1:2 (1kg of PRA for 2 liters of water)

Applications

Removal of interior paints, exterior coatings, multi-surface enamels, and water-based spray paints from the surface of solar module glass.

Instructions of use

1. **Dilute** the Paint Removal Agent concentrate with the correct amount of water (see dilution above);
2. **Apply** the diluted product directly to the affected areas, making sure that the surface is covered;
3. **Leave** the product to act for 10 to 15 minutes;
4. **Brush** the area to remove the paint residue. If necessary, repeat steps 2, 3 and 4 until all residues are properly removed;
5. **Rinse** the module thoroughly with water, making sure that all excess product is removed.

Comments

Please follow the instructions on the safety data sheet for safe handling of the product.

Properties

Appearance: Colorless transparent liquid;

Odor: Characteristic - solvent;

Solubility in water: Fully miscible in water.

Packaging

Transparent packages of 2, 5, and 20 kg, and IBC of 1000 kg.